

MULTIRAY INFRARED DETECTOR



M3535 - SERIES

WALL PLUGS MOUNTING



0° 1.6M height

Detection Pets Area





FEATURES

1. Outdoor & indoor installation.
2. Dual optical infrared detection.
3. Digital low frequency filtering.
4. Auto sensitivity adjustment.
5. Latest technology on PIR detection.
6. 24 month local factory warranty.
7. Free Installers training.

Installation Notes:


- *Do not install unit facing public roads, unless property has high walls.
- *Unit must be installed 2m radius away from plants.
- * Front screw is for tamper proofing.
- *To adjust direction, use bracket supplied.

Alternative Detection for Standard Coverage Lens



SPECIFICATIONS

1. Operating Voltage: 9 -18 volts DC.
2. Current: 8mA N/O - 18mA N/C.
3. Tamper Output: N/C.
4. Relay N/C N/O output switchable.
5. Temperature Range: -10°C to +65°C.
6. Walk Test: Red LED switchable.
7. Dimensions: 195 x 85 x 60mm.
8. 1.3m height normal installation.
9. 1.6m height pet avoidance.
10. Viewing Angle: 102°, 8-12M.
11. Warm Up Period: 20 seconds.
12. System UV protected.



0° 1.3M standard height

CONNECTION DIAGRAM

Wiring Connector

