#### **MULTIRAY INDOOR WIRELESS** W200W - SERIES

# button ge ĭ 2.2M height normal installation

#### **SPECIFICATIONS**

- Operating Voltage: 3.6 volts DC long duration lithium battery.

  2. Current: 20µA standby.

- Dimensions:90 x 55 x 50mm. Viewing Angle: 102°, 8-15M. System UV protected.

- Pet friendly adjustment

# Tamper Output: internally connected. . Temperature Range: -10°C to +65°C. . Walk Test: LED switchable. TX button inside MULTIRAY

Detection Pets Area

ew of detection heams

#### **SPECIFICATIONS**

- Operating Voltage: 3.7 volts DC lithium rechargeable battery.
   Build-in high efficience charger

- through solar panel .

  3. Current: 40µA standby.

  4. Tamper Output: internally connected.
- Temperature Range: -10°C to +65°C. Walk Test: LED switchable.
- 7. Dimensions:195 x 85 x 60mm. 8. Viewing Angle: 102°, 8-15M. 9. System UV protected.

1.3M height normal installation from the centre of the unit

**W4040 - SERIES** 

### Room Alert Alarm Receiver Remotely Operated





Up to 3 Remote Controls & 4 wireless detectors

This receiver can be used as an early warning device You can plug it into the USB of your computer or you can connect it to the power with the above adaptor. Any movement on your outdoor or indoor wireless detectors, you will be warned inside your house by it.

#### **FEATURES**

Outdoor installation.
 Dual optical infrared detection.

**MULTIRAY OUTDOOR WIRELESS** 

- 3. Digital low frequency filtering.

- Auto sensitivity adjustment.
   2 or 3 pulses adjustable.
   Latest technology on PIR detection.
   24 month local factory warranty.
   Free Installers training.

#### Installation Notes:

- \*Do not install unit facing public roads, unless property has high walls.
  \*Unit must be installed 2m radius away from plants.

- \* Front screw is for tamper & water proofing.


  \* For wall mounting drill with 3mm bit on internal marks.


  \*To adjust direction, use bracket supplied.

- \* 99% immunity to false alarms.
  \* To block a portion of detection area, use tape.
- \* Unit can be interfaced to existing alarm systems through 3 channel coded receiver, optional.

Manufactured in South Africa by Eurolock Security Systems Email:info@eurolock.com

#### **MULTIRAY INDOOR WIRELESS** W200W - SERIES






#### **SPECIFICATIONS**

- Operating Voltage: 3.6 volts DC long duration lithium battery.
- . Current: 20µA standby. . Tamper Output: internally connected.
- Temperature Range: -10°C to +65°C.
- Walk Test: LED switchable.
  Dimensions:90 x 55 x 50mm.

- Viewing Angle: 102°, 8-15M.
  System UV protected.
  Pet friendly adjustment.

#### **MULTIRAY OUTDOOR WIRELESS W4040 - SERIES**



#### **SPECIFICATIONS**


- 1. Operating Voltage: 3.7 volts DC lithium rechargeable battery.
- 2. Build-in high efficience charger through solar panel
- 3. Current: 40µA standby.
  4. Tamper Output: internally connected.
- Temperature Range: -10°C to +65°C.
- Walk Test: LED switchable.
   Dimensions: 195 x 85 x 60mm.
   Viewing Angle: 102°, 8-15M.
   System UV protected.

1.3M height normal installation from the centre of the unit

# Learning button on the back of the unit MULTIRAY Input 16Vol<u>t dc</u> Cha<u>nnel 1</u> O Channel 2 O Channel 3 O Channel 3 O

## W40W Series Interface Receiver to existing alarm systems

Can learn up to 7 wireless outdoor or indoor detectors.



- **FEATURES**1. Outdoor installation.
- 2. Dual optical infrared detection.
- Digital low frequency filtering.
   Auto sensitivity adjustment.
- 5. 2 or 3 pulses adjustable.
  6. Latest technology on PIR detection.
  7. 24 month local factory warranty.
- 8. Free Installers training.

- Installation Notes:
  \*Do not install unit facing public roads, unless property has high walls.

- \*Unit must be installed 2m radius away from plants.

  \* Front screw is for tamper & water proofing.

  \* For wall mounting drill with 3mm bit on internal marks.
- \*To adjust direction, use bracket supplied. \* 99% immunity to false alarms.
- \* To block a portion of detection area, use tape.
- \* Unit can be interfaced to existing alarm systems through 3 channel coded receiver, optional.

Manufactured in South Africa by Eurolock Security Systems Email:info@eurolock.com